

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it



Technical Datasheet

tasker® C285 – 1x0,50 mm²

Guitar Cable with Carbon Screen



A	B	C	D	E
---	---	---	---	---

CATEGORY Guitar Cable (See Audio Catalogue)
APPLICATIONS Premade cables for instrumental cable like Guitar, Bass and Keyboards

- A:** Soft Black PVC. Outer cable Diam. Ø 6,20 ± (0,20) mm.
- B:** First shielding with O.F.C. red copper Spiral covering 100%.
- C:** Second shielding with conductive carbon screen.
- D:** Transparent PPE insulation with outside diameter Ø: 1,70 ± (0,20) mm.
- E:** O.F.C. stranded red copper formation 7x0,30 mm.
 Nom. Cross section 1x 0,50 mm².

MARKING **tasker®** C285 1x0,50 PROFESSIONAL NOISELESS GUITAR CABLE LOW CAPACITY
CUSTOM This product may be custom produced also in **L.S.Z.H.** polymer, **PE, PUR,**
PRODUCTION with or without Metallic Armor.

Cable Properties

Conductor Resistance	38 Ω/km
Capacity Core/Shield	110 pF/mt
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			